



TECHNICAL DATA SHEET

PD 29 - RACE PODIUM

OVERVIEW

For ON-ROAD use on urban and paved roads. The PD 29 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	80/100-14	Internal code	800020001
Load Index and Speed Rating	49 L REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

PD 29 - RACE PODIUM

OVERVIEW

For ON-ROAD use on urban and paved roads. The PD 29 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	2.50-17	Internal code	800020002
Load Index and Speed Rating	43 L REINF	Application	M/C
Mounting	TT	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

PD 29 - RACE PODIUM

OVERVIEW

For ON-ROAD use on urban and paved roads. The PD 29 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	2.75-17	Internal code	800020003
Load Index and Speed Rating	47 P REINF	Application	M/C
Mounting	TT	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

PD 29 - RACE PODIUM

OVERVIEW

For ON-ROAD use on urban and paved roads. The PD 29 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	2.75-18	Internal code	800020004
Load Index and Speed Rating	48 P REINF	Application	M/C
Mounting	TT	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

PD 29 - RACE PODIUM

OVERVIEW

For ON-ROAD use on urban and paved roads. The PD 29 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	90/90-18	Internal code	800020005
Load Index and Speed Rating	57 P REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

PD 29 - RACE PODIUM

OVERVIEW

For ON-ROAD use on urban and paved roads. The PD 29 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	90/80-16	Internal code	800020007
Load Index and Speed Rating	55 J REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

PD 29 - RACE PODIUM

OVERVIEW

For ON-ROAD use on urban and paved roads. The PD 29 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	70/90-16	Internal code	800020008
Load Index and Speed Rating	42 P REINF	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

PD 29 - RACE PODIUM

OVERVIEW

For ON-ROAD use on urban and paved roads. The PD 29 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	3.25-16	Internal code	800020009
Load Index and Speed Rating	55 P REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.