



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	60/100-12	Internal code	800070014
Load Index and Speed Rating	36 M	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	1,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	60/100-14	Internal code	800070008
Load Index and Speed Rating	29 M	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	1,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	70/100-17	Internal code	800070016
Load Index and Speed Rating	40 M	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	70/100-19	Internal code	800070001
Load Index and Speed Rating	42 M	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	80/100-21	Internal code	800070003
Load Index and Speed Rating	51 M	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	90/90-21	Internal code	800070011
Load Index and Speed Rating	54 M	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	70/100-10	Internal code	800070013
Load Index and Speed Rating	38 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	1,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	70/100-12	Internal code	800070009
Load Index and Speed Rating	50 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	90/100-14	Internal code	800070015
Load Index and Speed Rating	49 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	2,8 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	90/100-16	Internal code	800070002
Load Index and Speed Rating	51 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	100/100-18	Internal code	800070006
Load Index and Speed Rating	51 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	110/100-18	Internal code	800070004
Load Index and Speed Rating	64 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	120/90-18	Internal code	800070007
Load Index and Speed Rating	71 M REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,8 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	100/90-19	Internal code	800070010
Load Index and Speed Rating	57 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	110/90-19	Internal code	800070005
Load Index and Speed Rating	62 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT

NOT RECOMMENDED

UNPAVED / GRAVEL

GOOD

UNEVEN / OFF-ROAD

EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

RMX 35 - EXTREME

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The RMX 35 line stands out for its balance of performance and durability and offers a complete range of sizes, including sizes for minibikes.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	120/90-19	Internal code	800070012
Load Index and Speed Rating	66 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	6,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)