



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces.

Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	2.75-18	Internal code	800070009
Load Index and Speed Rating	42 P	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	90/90-19	Internal code	800070010
Load Index and Speed Rating	52 T	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	80/90-21	Internal code	800070006
Load Index and Speed Rating	48 T	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	90/90-21	Internal code	800070007
Load Index and Speed Rating	54 S	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,8 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	2.75-17	Internal code	800070013
Load Index and Speed Rating	47 P REINF	Application	M/C
Mounting	TT	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	2.50-17	Internal code	800070014
Load Index and Speed Rating	43 L REINF	Application	M/C
Mounting	TT	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	80/100-14	Internal code	800070015
Load Index and Speed Rating	49 L	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	110/90-17	Internal code	800070001
Load Index and Speed Rating	60 P	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	120/90-17	Internal code	800070002
Load Index and Speed Rating	64 P	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATION

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	130/80-17	Internal code	800070011
Load Index and Speed Rating	65 P	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	6,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	90/90-18	Internal code	800070008
Load Index and Speed Rating	57 P REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	110/80-18	Internal code	800070003
Load Index and Speed Rating	57 P REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATION

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	120/80-18	Internal code	800070004
Load Index and Speed Rating	62 S	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

R 34 - RALLYE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 80/20.

The R34 line features a tread pattern designed for riding long distances while providing traction and stability on both types of surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	130/80-18	Internal code	800070012
Load Index and Speed Rating	66 P	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	6,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus