



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces.

Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	100/80-17	Internal code	800100003
Load Index and Speed Rating	52 T	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces.

Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	130/70-17	Internal code	800100004
Load Index and Speed Rating	62 T	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces.

Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	90/90-18	Internal code	800100005
Load Index and Speed Rating	57 P REINF	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces.

Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	80/100-18	Internal code	800100006
Load Index and Speed Rating	47 P	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces.

Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	110/70-17	Internal code	800100007
Load Index and Speed Rating	54 T	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces.

Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	140/70-17	Internal code	800100008
Load Index and Speed Rating	66 T	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	6,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces.

Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	100/80-18	Internal code	800100009
Load Index and Speed Rating	53 P	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces.

Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	90/90-14	Internal code	800100010
Load Index and Speed Rating	46 P	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces.

Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	110/90-14	Internal code	800100011
Load Index and Speed Rating	57 P REINF	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	120/70-13	Internal code	800840001
Load Index and Speed Rating	57 L	Application	M/C
Mounting	TL	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	130/70-12	Internal code	800840002
Load Index and Speed Rating	56 L	Application	M/C
Mounting	TL	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	130/60-13	Internal code	800840003
Load Index and Speed Rating	60 P REINF	Application	M/C
Mounting	TL	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATION

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	90/90-12	Internal code	800840004
Load Index and Speed Rating	44 J	Application	M/C
Mounting	TL	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	100/90-10	Internal code	800840005
Load Index and Speed Rating	56 J	Application	M/C
Mounting	TL	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

HB 37 - HIGH BORN

OVERVIEW

For ON-ROAD use on urban and paved roads. The HB 37 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	120/70-12	Internal code	800840006
Load Index and Speed Rating	56 L	Application	M/C
Mounting	TL	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.