



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	80/100-18	Internal code	800150014
Load Index and Speed Rating	47 P	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	2.75-18	Internal code	800150003
Load Index and Speed Rating	42 P	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	60/100-17	Internal code	800150017
Load Index and Speed Rating	33 L	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	90/90-17	Internal code	800150020
Load Index and Speed Rating	49 P	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	100/90-18	Internal code	800150007
Load Index and Speed Rating	56 P	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATION

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	110/80-14	Internal code	800150018
Load Index and Speed Rating	59 P REINF	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATION

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	90/90-18	Internal code	800150004
Load Index and Speed Rating	51 P	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	80/100-14	Internal code	800150005
Load Index and Speed Rating	49 L REINF	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	120/80-17	Internal code	800150021
Load Index and Speed Rating	61 P	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	150/60-17	Internal code	800150019
Load Index and Speed Rating	66 R	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	6,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	110/70-17	Internal code	800150024
Load Index and Speed Rating	54 S	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	70/90-17	Internal code	800150022
Load Index and Speed Rating	43 L	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	120/70-14	Internal code	800150009
Load Index and Speed Rating	61 P	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	130/70-13	Internal code	800150013
Load Index and Speed Rating	63 P	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	110/70-14	Internal code	800150023
Load Index and Speed Rating	56 P	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	90/80-14	Internal code	800150011
Load Index and Speed Rating	49 P	Application	M/C
Mounting	TL	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	100/80-14	Internal code	800150008
Load Index and Speed Rating	48 P	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATION

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	80/80-14	Internal code	800150010
Load Index and Speed Rating	43 P REINF	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

SS 48 - SUPER STREET

OVERVIEW

For ON-ROAD use on urban and paved roads. The SS 48 line features a high-performance sporty design for both dry and wet surfaces. Designed for scooters

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	110/70-13	Internal code	800150012
Load Index and Speed Rating	48 P	Application	M/C
Mounting	TL	Mounting position	Front
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus