



TECHNICAL DATA SHEET

RT 36 - TRAIL

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or uneven terrain (gravel or hard-packed dirt) – 60/40.

The RT 36 line features a tread pattern with blocks that enhance traction without compromising performance on on-road sections. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	110/90-17	Internal code	800090004
Load Index and Speed Rating	60 P	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,8 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	GOOD

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

RT 36 - TRAIL

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or uneven terrain (gravel or hard-packed dirt) – 60/40.

The RT 36 line features a tread pattern with blocks that enhance traction without compromising performance on on-road sections. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	90/90-18	Internal code	800090005
Load Index and Speed Rating	51 P	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	GOOD

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

RT 36 - TRAIL

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or uneven terrain (gravel or hard-packed dirt) – 60/40.

The RT 36 line features a tread pattern with blocks that enhance traction without compromising performance on on-road sections. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	110/80-18	Internal code	800090002
Load Index and Speed Rating	58 P	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	GOOD

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

RT 36 - TRAIL

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or uneven terrain (gravel or hard-packed dirt) – 60/40.

The RT 36 line features a tread pattern with blocks that enhance traction without compromising performance on on-road sections. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	120/80-18	Internal code	800090007
Load Index and Speed Rating	62 P	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,2 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	GOOD

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

RT 36 - TRAIL

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or uneven terrain (gravel or hard-packed dirt) – 60/40.

The RT 36 line features a tread pattern with blocks that enhance traction without compromising performance on on-road sections. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	80/100-18	Internal code	800090008
Load Index and Speed Rating	47 P	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	GOOD

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

RT 36 - TRAIL

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or uneven terrain (gravel or hard-packed dirt) – 60/40. The RT 36 line features a tread pattern with blocks that enhance traction without compromising performance on on-road sections. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	90/90-19	Internal code	800090003
Load Index and Speed Rating	52 P	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	GOOD

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

RT 36 - TRAIL

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or uneven terrain (gravel or hard-packed dirt) – 60/40. The RT 36 line features a tread pattern with blocks that enhance traction without compromising performance on on-road sections. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	80/90-21	Internal code	800090001
Load Index and Speed Rating	48 P	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	4,8 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	GOOD

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

RT 36 - TRAIL

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or uneven terrain (gravel or hard-packed dirt) – 60/40. The RT 36 line features a tread pattern with blocks that enhance traction without compromising performance on on-road sections. Designed for low- and mid-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	90/90-21	Internal code	800090006
Load Index and Speed Rating	54 P	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	GOOD

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)