



TECHNICAL DATA SHEET

SH 31 - STEEL HORSE

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads.
The SH 31 line stands out for its balance of performance and durability.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	60/100-17	Internal code	800040009
Load Index and Speed Rating	33 M	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

SH 31 - STEEL HORSE

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The SH 31 line stands out for its balance of performance and durability.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	2.75-18	Internal code	800040005
Load Index and Speed Rating	42 M	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

SH 31 - STEEL HORSE

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The SH 31 line stands out for its balance of performance and durability.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	90/90-19	Internal code	800040006
Load Index and Speed Rating	52 M	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

SH 31 - STEEL HORSE

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The SH 31 line stands out for its balance of performance and durability.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	3.00-21	Internal code	800040004
Load Index and Speed Rating	51 M	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,6 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

SH 31 - STEEL HORSE

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The SH 31 line stands out for its balance of performance and durability.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	80/100-14	Internal code	800040008
Load Index and Speed Rating	49 M REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

SH 31 - STEEL HORSE

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The SH 31 line stands out for its balance of performance and durability.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	100/90-17	Internal code	800040007
Load Index and Speed Rating	55 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

SH 31 - STEEL HORSE

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The SH 31 line stands out for its balance of performance and durability.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	4.00-17	Internal code	800040001
Load Index and Speed Rating	62 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

SH 31 - STEEL HORSE

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The SH 31 line stands out for its balance of performance and durability.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	90/90-18	Internal code	800040003
Load Index and Speed Rating	51 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

SH 31 - STEEL HORSE

OVERVIEW

For OFF-ROAD use in multiple applications, on all types of terrain and unpaved rural roads. The SH 31 line stands out for its balance of performance and durability.

PRODUCT LINE - OFF ROAD

TECHNICAL DATA

Size	4.00-18	Internal code	800040002
Load Index and Speed Rating	64 M	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	NOT RECOMMENDED
UNPAVED / GRAVEL	GOOD
UNEVEN / OFF-ROAD	EXCELLENT

CERTIFICATIONS

N/A

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)