



TECHNICAL DATA SHEET

BS 32 - BLACK SNAKE

OVERVIEW

For ON-ROAD use on urban and paved roads. The BS 32 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	2.75-18	Internal code	800050001
Load Index and Speed Rating	48 P REINF	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

BS 32 - BLACK SNAKE

OVERVIEW

For ON-ROAD use on urban and paved roads. The BS 32 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	90/90-18	Internal code	800050002
Load Index and Speed Rating	57 P REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

BS 32 - BLACK SNAKE

OVERVIEW

For ON-ROAD use on urban and paved roads. The BS 32 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	100/90-18	Internal code	800050003
Load Index and Speed Rating	56 P	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

BS 32 - BLACK SNAKE

OVERVIEW

For ON-ROAD use on urban and paved roads. The BS 32 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	80/100-14	Internal code	800050004
Load Index and Speed Rating	49 L REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

BS 32 - BLACK SNAKE

OVERVIEW

For ON-ROAD use on urban and paved roads. The BS 32 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	60/100-17	Internal code	800050005
Load Index and Speed Rating	33 L	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	1,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

BS 32 - BLACK SNAKE

OVERVIEW

For ON-ROAD use on urban and paved roads. The BS 32 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for low-displacement motorcycles.

PRODUCT LINE - ON ROAD

TECHNICAL DATA

Size	3.50-16	Internal code	800050006
Load Index and Speed Rating	58 P REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

BS 32 - BLACK SNAKE

OVERVIEW

For ON-ROAD use on urban and paved roads. The BS 32 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	3.50-10	Internal code	800830001
Load Index and Speed Rating	51 J	Application	M/C
Mounting	TT	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	2,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

BS 32 - BLACK SNAKE

OVERVIEW

For ON-ROAD use on urban and paved roads. The BS 32 line features a traditional tread pattern that provides grip and performance to withstand the demands of daily use. Designed for scooters.

PRODUCT LINE - SCOOTER

TECHNICAL DATA

Size	3.00-10	Internal code	800830002
Load Index and Speed Rating	42 J	Application	M/C
Mounting	TT	Mounting position	DUAL (FRONT/REAR)
Construction	Diagonal	Weight (approx.)	1,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	EXCELLENT
UNPAVED / GRAVEL	NOT RECOMMENDED
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals. For warehouse storage, the use of circular racks is recommended. After mounting, lift the wheel off the ground to relieve the load on the tires. Mounted tires must have their pressure checked periodically.