



TECHNICAL DATA SHEET

WH 21 — WLD HORSE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 70/30. The WH21 line features a tread pattern with low bars and blocks that provide traction and stability on both types of surfaces. Designed for low-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	80/100-14	Internal code	800010001
Load Index and Speed Rating	49 L REINF	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	2,4 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
[@rinaldipneus](https://www.instagram.com/rinaldipneus)



TECHNICAL DATA SHEET

WH 21 — WLD HORSE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 70/30. The WH21 line features a tread pattern with low bars and blocks that provide traction and stability on both types of surfaces. Designed for low-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	4.60-17	Internal code	800010002
Load Index and Speed Rating	62 R	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

WH 21 — WLD HORSE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 70/30. The WH21 line features a tread pattern with low bars and blocks that provide traction and stability on both types of surfaces. Designed for low-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	4.10-18	Internal code	800010003
Load Index and Speed Rating	60 R	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	4,2 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

WH 21 — WLD HORSE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 70/30. The WH21 line features a tread pattern with low bars and blocks that provide traction and stability on both types of surfaces. Designed for low-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	90/90-18	Internal code	800010004
Load Index and Speed Rating	51 P	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

WH 21 — WLD HORSE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 70/30. The WH21 line features a tread pattern with low bars and blocks that provide traction and stability on both types of surfaces. Designed for low-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	2.75-21	Internal code	800010005
Load Index and Speed Rating	45 R	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT

GOOD

UNPAVED / GRAVEL

EXCELLENT

UNEVEN / OFF-ROAD

NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.

RINALDI®

Technical Manager:
Camila Taliotto Scarton

Rinaldi S.A - Indústria de Pneumáticos
Rua Luiz Alegretti, 193, Bento Gonçalves / RS - Brazil, 95705-890
www.rinaldi.com.br
@rinaldipneus



TECHNICAL DATA SHEET

WH 21 — WLD HORSE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 70/30. The WH21 line features a tread pattern with low bars and blocks that provide traction and stability on both types of surfaces. Designed for low-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	3.00-21	Internal code	800010006
Load Index and Speed Rating	51 R	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT

GOOD

UNPAVED / GRAVEL

EXCELLENT

UNEVEN / OFF-ROAD

NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

WH 21 — WLD HORSE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 70/30. The WH21 line features a tread pattern with low bars and blocks that provide traction and stability on both types of surfaces. Designed for low-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	90/90-19	Internal code	800010007
Load Index and Speed Rating	52 R	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	3,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT

GOOD

UNPAVED / GRAVEL

EXCELLENT

UNEVEN / OFF-ROAD

NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

WH 21 — WLD HORSE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 70/30. The WH21 line features a tread pattern with low bars and blocks that provide traction and stability on both types of surfaces. Designed for low-displacement motorcycles.

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	110/90-17	Internal code	800010008
Load Index and Speed Rating	60 R	Application	M/C
Mounting	TT	Mounting position	Rear
Construction	Diagonal	Weight (approx.)	5,0 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT	GOOD
UNPAVED / GRAVEL	EXCELLENT
UNEVEN / OFF-ROAD	NOT RECOMMENDED

CERTIFICATIONS

INMETRO, UNECE R75

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.



TECHNICAL DATA SHEET

WH 21 — WLD HORSE

OVERVIEW

Mixed use (ON/OFF DUAL), alternating between urban and paved roads and compacted or slightly uneven terrain (gravel or hard-packed dirt) – 70/30. The WH21 line features a tread pattern with low bars and blocks that provide traction and stability on both types of surfaces. Designed for low-displacement motorcycles

PRODUCT LINE - ON/OFF DUAL

TECHNICAL DATA

Size	2.75-18	Internal code	800010009
Load Index and Speed Rating	42 P	Application	M/C
Mounting	TT	Mounting position	Front
Construction	Diagonal	Weight (approx.)	2,5 kg
NCM	40114000	Warranty	5 years

TERRAIN

PAVED / ASPHALT

GOOD

UNPAVED / GRAVEL

EXCELLENT

UNEVEN / OFF-ROAD

NOT RECOMMENDED

CERTIFICATIONS

INMETRO

STORAGE INSTRUCTIONS

Store in a clean, dry, well-ventilated area. Keep away from sources of heat, ozone or chemicals.
For warehouse storage, the use of circular racks is recommended.
After mounting, lift the wheel off the ground to relieve the load on the tires.
Mounted tires must have their pressure checked periodically.